



V-STRIM 250 SX



#FEELSUZUKIPOWER

V-STROM SX250 SPECIFICATIONS

Overall length	2.180 mm
Overall width	880 mm
Overall height	1.355 mm
Wheelbase	1.440 mm
Ground clearance	205 mm
Seat height	835 mm
Curb mass	167 kg
Engine type	4-stroke, 1-cylinder, oil-cooled, SOHC
Bore x Stroke	76,0 x 54,9 mm
Engine displacement	249 cm ³
Fuel system	Fuel injection
Starter system	Electric
Transmission	6-speed constant mesh
Suspension	Front Telescopic, Cylindrical Coil, Oil Damped
	Rear Swingarm type, Cylindrical Coil, Oil Damped
Rake / Trail	27° / 97 mm
Brake	Front Disc, single
	Rear Disc, single
Tires	Front 100/90-19M/C 57S, tubeless
	Rear 140/70-17M/C 66S, tubeless
Ignition system	Electronic ignition
Fuel tank capacity	12 L



Champion Yellow



Pearl Glacier White



Pearl Fresh Blue



Glass Sparkle Black



#FEEL
SUZUKI
POWER

Anjuran Safety Riding

- Gunakan Helm SNI dan kencangkan tali pengikat dengan benar.
- Gunakan jaket lengan panjang, sepatu yang nyaman dan sarung tangan selama berkendara.
- Taati peraturan serta rambu-rambu lalu lintas demi keselamatan dan keamanan selama berkendara di jalan.
- Hindari berkendara jika mengonsumsi alkohol atau obat-obatan.
- Hindari berkendara sambil bertelephone atau SMS
- Hindari berkendara dalam keadaan mengantuk.

Sale distributor

PT SUZUKI INDOMOBIL SALES
JL. Raya Bekasi km. 19 Pulogadung - Jakarta 13920



GUNAKAN SELALU

ECSTAR

- Gunakan selalu suku cadang asli SUZUKI
- Periksa Oli secara berkala dan pakailah Oli ECSTAR
- Lakukan perawatan secara berkala di bengkel resmi SUZUKI



Bebas Pulsa, 24 Jam Siaga Melayani Anda
0800 1100 800

CERTIFICATE NO. Q 18672



Find us on
Suzuki Motorcycles Indonesia



suzukiindonesiamotor



Suzuki Motorcycles Indonesia



suzukiindonesiamotor

www.suzuki.co.id



Bacalah buku petunjuk pemilik dengan seksama sebelum berkendara